

## VARIFAN ELECTRONIC TEMPERATURE/ SPEED CONTROLS

### ECS CONTROLS

- ▶ VARIABLE STAGE ▶ ALARM CONTACTS ▶ MOTOR CURVES
- ▶ HI-LO READINGS ▶ TEMP RAMPING ▶ 120/240 VOLT

PART #	MODEL #	DESCRIPTION	PROBE (LENGTH)
E53-8100	ECS-1M	1 STAGE DIGITAL - 1 VARIABLE STAGE (10 AMP.)	2004-1K/30 (30')
E53-8200	ECS-2M	2 STAGE DIGITAL - 1 VARIABLE STAGE (10 AMP.) 1 ON/OFF STAGE-10 AMP. (HEATING OR COOLING)	2004-1K/30 (30')
E53-8300	ECS-3M	3 STAGE DIGITAL - 2 VARIABLE STAGES (6 AMPS EA.) 1 ON/OFF STAGE (10 AMP.) (HEATING OR COOLING)	2004-1K/30 (30')
E53-8400	ECS-4M	4 STAGE DIGITAL - 2 VARIABLE STAGES (6 AMPS EA.) 1 ON/OFF STAGE (10 AMP.) (COOLING, SPRINKLER), 1 ON/OFF STAGE (10 AMP.) (HEATING OR COOLING)	2004-1K/30 (30')
E53-8500	ECS-5M	5 STAGE DIGITAL - 2 VARIABLE STAGES (6 AMP. EA.) 2 ON/OFF STAGES (10 AMP. EA.) (COOLING) 1 ON/OFF STAGE (10 AMP.) (HEATING OR COOLING)	2004-1K/30 (30')
E53-8650	DIP-1	DIGITAL INLET POSITIONER - FOR 24V ACTUATOR WITH POTENTIOMETER FEEDBACK, 24 VOLT POWER SUPPLY INCLUDED (MUST BE USED IN CONJUNCTION WITH ONE OR TWO ECS-'M' CONTROLS)	2004-1K (10")

### ECS-C CONTROLS

- ▶ IMPROVED ENCLOSURE ▶ LIGHTENING PROTECTION.
- ▶ UP TO 4 PROBES CAN BE CONNECTED (2 INCLUDED WITH EACH CONTROL)
- ▶ 8AMP VARIABLE STAGES ▶ 10AMP RELAYS
- ▶ **REQUIRES 240V SUPPLY & 240V VARIABLE STAGE FANS**
- ▶ **CORE 100 TECHNOLOGY**



PART #	MODEL #	DESCRIPTION	PROBE (LENGTH)
E53-8300C	ECS-3C	2 VARIABLE, 1 OFF/ON RELAY - HEAT & COOL OR MIST (2 PROBES INCLUDED)	2004-10K (10") 2004-10K/30 (30')
<b>E53-8301C</b>	<b>ECS-3C/120</b>	<b>120VOLT - SPECIAL FOR 120VOLT FANS</b>	SAME AS ECS-3C
E53-8500C	ECS-5C	2 VARIABLE, 3 OFF/ON RELAYS - 2 HEAT, 3 COOL 1 MIST (2 PROBES INCLUDED)	2004-10K (10") 2004-10K/30 (30')
E53-8650C	DIP-1C	INLET POSITIONER, 120/240V	2004-10K (10")
E53-3401C	SA-10C	1 STAGE VARIABLE - <b>NON DIGITAL</b>	2004-10K (10")
E53-4670	RH-3	RELATIVE HUMIDITY PROBE **REQUIRES 1 WIRE HARNESS	N/A
E53-4677		**RED WIRE HARNESS ("C" CONTROLS)	
E53-4675		**BLUE WIRE HARNESS ("M" CONTROLS)	
E53-4676		**YELLOW WIRE HARNESS (MSC/IC/LX CONTROLS)	
E53-9849	MM-4	UPLOAD/DOWNLOAD MEMORY STICK	

**PROVIDE A MINIMUM OF 1 T15-WD FOR SAFETY BACK-UP ON EACH CONTROL**

2 YEAR WARRANTY UNLESS NOTED OTHERWISE